

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4383>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.700 inches

Thickness:

4.000 inches

Length:

20.580 inches

End Application:

Missile, minuteman Igm-30

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Roughly rectangular with cutout on right/long edge: 3.98wx1.50h, 1.78 from bottom & adjacent cutout: 1.48wx1.78h at bottom corner; left edge has cutout 4.22wx1.50h, 1.78 from bottom & cutout 2.50wx1.78h at left bottom corner; a circular cutout near center with 7.00 inch diameter centered 8.97 from left & 8.79 from top; long edges have curved grooves: 2.50wx2.50d on left edge with 1.50 radius on inner edge & 2.50wx2.50d on right edge with 1.50 radius on inner edge, widening near top to left with arc with 6.50 radius centered 8.97 from left & 4.78 from top; near side is marked "fwd up" at center top & with part number at bottom right

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d