## NSN 9330-01-502-4383

Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-4383

Fire Retarding Characteristic:
Not fire retarding
Width:
17.700 inches
Thickness:
4.000 inches
Length:
20.580 inches
End Application:
Missile, minuteman Igm-30
Surface Condition:
Rough
Density Rating:
1.2 pounds per cubic foot
Compression Strength At 25 Pct Deflection:
0.35 pounds per square inch
Product Name:
Filler foam
Special Features:
Roughly rectangular with cutout on right/long edge: 3.98wx1.50h, 1.78 from bottom & adjacent cutout: 1.48wx1.78h at bottom corner; left
edge has cutout 4.22wx1.50h, 1.78 from bottom & cutout 2.50wx1.78h at left bottom corner; a circular cutout near center with 7.00 inch
diameter centered 8.97 from left & 8.79 from top; long edges have curved grooves: 2.50wx2.50d on left edge with 1.50 radius on inner edge
& 2.50wx2.50d on right edge with 1.50 radius on inner edge, widening near top to left with arc with 6.50 radius centered 8.97 from left & 4.78
from top; near side is marked "fwd up" at center top & with part number at bottom right
Material:
Plastic, polyurethane
Material:
Plastic polyurethane
Supplementary Features:
Material to be reticulated foam per sm-alc specification ms-mmrs-87-100
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
T258-d