

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4449>

Fire Retarding Characteristic:

Not fire retarding

Width:

14.500 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on left/short edge: 1.25wx1.34h, 1.72 from bottom edge & 1.25wx1.04h, 2.10 from top; lengthwise cutout 2.10wx1.25d along top edge; semicircular groove running parallel to long edges for 10.80 inches from left edge with 2.00 inch radius centered 6.40 from bottom edge & 0.50 from top surface; near side is marked "up" & "fwd" on 2 lines at center top & with part number in bottom right corner; far side is tapered 0.25 at top edge & 0.40 at bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d