

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4462>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.660 inches

Thickness:

4.000 inches

Length:

20.890 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular; right/short edge has 2 cutouts: 1.25wx2.70h at bottom corner & 1.25wx3.66h at top right corner & a crosswise groove: 1.25wx1.70h along right edge; top edge is tapered 0.76 at near side; far side has cutout: 4.10wx7.35hx1.80d in upper right corner (far side up) & lengthwise grooves: 1.68wx1.76d along top edge & 2.70wx1.76d along bottom edge & is marked "up aft" in upper left corner & with part number centered above bottom groove

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d