

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4924>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.300 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on left/short edge: 1.25wx1.20h, 2.20 from top & 2.64wx4.20h at bottom left corner; bottom tapers 0.50 toward far side & has cutout 0.80w, 1.68 from right edge, extending to left edge & following angle of taper; top edge has 2 cutouts: 2.03wx1.25h, 8.53 from right & arch 6.74wx12.30h, 8.13 from left ending in circle with 3.37 radius; far side has lengthwise groove 2.20wx1.68h along top edge & is marked "up" & "aft" on 2 lines in upper left area (far side up) and with part number in upper right area

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d