

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4940>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

15.400 inches

**Thickness:**

2.500 inches

**Length:**

20.940 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 3 cutouts on left edge: 1.12wx1.44h, 1.44 from bottom, 1.12wx1.06h, 7.50 from bottom & 1.12wx1.40h, 12.04 from bottom; top edge tapers 0.65 from far to near side; a 2.50 inch diameter circle punched out, centered 3.50 from left & 5.20 from top with line cut through from circle to left edge, 5.20 from bottom; near side has 2 lengthwise grooves: 1.10wx1.26d, 6.86 & 13.60 from left; far side has rounded cutout with 7.75 radius, centered 10.62 from left, extending from top edge for 56.40 inches & has markings: "up" & "aft" in upper left corner (far side up) & with part number in lower left corner

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d