Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-4972

Fire Retarding Characteristic:

Not fire retarding

Width:

16.000 inches

Thickness:

4.000 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with numerous cutouts: one on right/short side: 5.24wx6.80h at top corner; 2 cutouts on left side: 1.25wx2.56h, 1.84 from bottom & 4.70wx11.70h, 4.30 from bottom; near side has rounded cutout at top edge 1.80w with radius of 4.25 centered 5.64 from left (cutoff) edge; far side has lengthwise groove: 2.16wx2.28d along bottom edge & is marked "up" & "aft" at center top (far side up) & with part number centered above bottom groove

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T258-d