

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4986>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.280 inches

Thickness:

4.000 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 3 cutouts on left/short edge: 1.26wx1.24h, 2.16 from bottom & 3.30wx4.86h, 5.00 from bottom & 4.90wx3.50h, 9.10 from bottom; 2 cutouts on right edge: 2.40wx3.50h, 9.10 from bottom & 4.90wx3.50hx1.08d, 9.10 from bottom; top edge tapers 0.40 from far to near surfaces; far side has crosswise grooves: 2.32wx1.50d along top edge & 2.15wx2.36d along bottom one & lengthwise u-shaped groove beginning 3.60 from left edge & 2.32 from top edge at surface (far side up), down & to right to 5.60 from left & 1.50 from surface horizontal to right 4.00 inches, up to 11.60 from left, 1.50 from surface, then right 4.06 then perpendicularly up 1.50 inches then right to edge; far side is marked "up" & "aft" near center top & with part number at center bottom

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d