

View Online at <https://aerobasegroup.com/nsn/9330-01-502-5155>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.160 inches

Thickness:

4.000 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 1.40wx2.40h at top corner & 1.40wx2.24h at bottom corner; 2 cutouts on left edge: 1.26wx1.60h, 2.24 from bottom & 3.00wx3.70h at top corner; top edge has cutout 2.62wx3.70h, 4.10 from right; near side has lengthwise grooves: 3.70wx2.20d along top edge & 2.12wx0.68d along bottom edge & crosswise groove: 1.40wx2.68d along right edge; far side has lengthwise grooves: (far side up) 2.40wx0.68d along top edge & 2.24wx1.00d along bottom edge & cutout: 4.14wx6.32lx2.00d at right bottom corner & is marked "up" & "aft" in upper groove & with part number above lower groove

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d