

View Online at <https://aerobasegroup.com/nsn/9330-01-502-5555>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.440 inches

Thickness:

4.000 inches

Length:

19.800 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutout on bottom/long edge: 3.60w x4.40h at left corner; 2 cutouts on top edge: 2.60wx3.84h at left corner & 5.70wx4.24h at right corner; near side has 3 crosswise grooves: 1.16wx1.70d, 5.20 & 11.20 inches from left edge & 3.20wx2.12d along right edge; far side tapers 0.88 at bottom edge & has slanted cutout 5.70w from right edge (near side up) at near surface top edge, slanting down to 1.60 from top edge on far side & a cutout on bottom edge: 10.02wx1.36hx0.88d 5.50 from left & is marked: "up" & "aft" near center top & with part number in lower right area (near side up)

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d

Mil-std (military Standard):

Mil-prf-87260 spec.