

View Online at <https://aerobasegroup.com/nsn/9330-01-502-5573>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.600 inches

Thickness:

2.500 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on bottom/long edge: 1.80wx3.00h at right corner & 4.20wx4.60h at left corner; left edge has cutout: 1.26wx1.40h, 2.20 from top; top edge has 2 cutouts: rectangle, 3.50wx5.75h, 3.50 from right edge & half-arch, 2.00w extending to right of line 3.50 from right edge, ending in arc with 1.00 inch radius, centered 3.00 from right edge & 7.00 from top; near side has groove along top edge: 2.20wx1.50d; far side tapers 0.30 at bottom edge & is marked: "up" & "aft" on 2 lines below top groove, in right corner (far side up) & with part number centered near bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d