Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-5591

Fire Retarding Characteristic:

Not fire retarding

Width:

14.200 inches

Thickness:

4.000 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutout on right/short edge: 1.26wx1.00h, 4.00 inches from bottom edge; 2 cutouts on left edge: 1.26wx2.50h, 2.50 from bottom & 1.26wx1.40h, 2.08 from top; near side has 2 lengthwise grooves: rectangular, 2.08wx1.40d along top edge & semicircular with 2.00 inch radius centered 6.16 from bottom & 0.70 from near surface; near side is marked: "up" & "fwd" on 2 lines in upper left area (below groove) & with part number to the right; far side is chamfered 45 degrees, 0.50 inches at bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T258-d