

View Online at <https://aerobasegroup.com/nsn/9330-01-502-5610>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.380 inches

Thickness:

4.000 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with arched cutout on right/short edge: 2.05w, 3.40 from bottom, extending from right edge to left, ending in arc with 2.05 inch radius centered 9.75 from right; bottom edge has cutout: 8.79wx1.16hx0.94d, 6.40 from left; left edge has 3 cutouts: 1.26wx1.40h, 2.20 from top & 1.26wx0.78h, 2.72 from bottom & arched cutout with 2.50 radius centered 6.30 from bottom & 3.30 from left, extending to left edge; near side has lengthwise groove: 2.20wx1.40d along top edge & is marked: "up fwd" in upper left area below groove & with part number in top groove near right edge; far side tapers 0.30 at bottom edge & has semicircular lengthwise groove with 2.00 radius centered 6.88 from bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d