

View Online at <https://aerobasegroup.com/nsn/9330-01-502-5610>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

15.380 inches

**Thickness:**

4.000 inches

**Length:**

20.940 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with arched cutout on right/short edge: 2.05w, 3.40 from bottom, extending from right edge to left, ending in arc with 2.05 inch radius centered 9.75 from right; bottom edge has cutout: 8.79wx1.16hx0.94d, 6.40 from left; left edge has 3 cutouts: 1.26wx1.40h, 2.20 from top & 1.26wx0.78h, 2.72 from bottom & arched cutout with 2.50 radius centered 6.30 from bottom & 3.30 from left, extending to left edge; near side has lengthwise groove: 2.20wx1.40d along top edge & is marked: "up fwd" in upper left area below groove & with part number in top groove near right edge; far side tapers 0.30 at bottom edge & has semicircular lengthwise groove with 2.00 radius centered 6.88 from bottom edge

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d