

View Online at <https://aerobasegroup.com/nsn/9330-01-502-5635>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

15.400 inches

**Thickness:**

4.000 inches

**Length:**

23.400 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 2 cutouts on left/short edge: 1.25wx1.34h, 2.16 inches from bottom & 1.25wx1.16h, 2.20 from top; a cutout on bottom edge: 7.56wx0.32h, 6.80 inches from left edge; a circular punchout with 5.00 diameter, centered 9.04 from left & 6.70 from bottom with line cut through from center of circle to left edge; near side has lengthwise groove: 2.20wx1.36d along top edge & is marked: "up" & "fwd" on 2 lines in upper right area below groove & with part number in lower right corner; far side has lengthwise groove: 2.16wx1.60d along bottom edge & semicircular lengthwise groove with 2.00 radius centered 7.00 from bottom & extending from left edge to right, 9.04 inches

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d

**Mil-std (military Standard):**

Mil-prf-87260 spec.