

View Online at <https://aerobasegroup.com/nsn/9330-01-502-5635>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.400 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on left/short edge: 1.25wx1.34h, 2.16 inches from bottom & 1.25wx1.16h, 2.20 from top; a cutout on bottom edge: 7.56wx0.32h, 6.80 inches from left edge; a circular punchout with 5.00 diameter, centered 9.04 from left & 6.70 from bottom with line cut through from center of circle to left edge; near side has lengthwise groove: 2.20wx1.36d along top edge & is marked: "up" & "fwd" on 2 lines in upper right area below groove & with part number in lower right corner; far side has lengthwise groove: 2.16wx1.60d along bottom edge & semicircular lengthwise groove with 2.00 radius centered 7.00 from bottom & extending from left edge to right, 9.04 inches

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d

Mil-std (military Standard):

Mil-prf-87260 spec.