

View Online at <https://aerobasegroup.com/nsn/9330-01-502-5638>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.300 inches

Thickness:

2.500 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutout on top/long edge: 7.80wx2.50h, 9.20 inches from left edge; 2 cutouts on left edge: 1.35wx1.00h, 2.50 from top & 2.04wx3.60h at bottom corner; cutout on bottom edge: 19.30wx0.80h 1.10 from left edge; a circular punchout with 4.88 inch diameter centered 9.98 from left & 7.04 from bottom; near side has "up"& "fwd" in upper right corner & part number in lower right corner; far side tapers 0.36 at bottom edge (cutout on bottom edge follows this angle)

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d