

View Online at <https://aerobasegroup.com/nsn/9390-00-009-8802>

Cross Sectional Shape:

Open channel with round base

Nonmetallic Hardness Rating:

45.0 shore durometer a and 55.0 shore durometer a

Min. Tensile Strength (psi):

1000 pounds per square inch

Temperature Rating:

-67.0 degrees fahrenheit

Overall Height:

0.620 inches

Length:

120.000 inches

Left Side Flange Thickness:

0.030 inches

Right Side Flange Thickness:

0.030 inches

Environmental Protection:

Low temperature and ozone resistant

First Slot/groove Depth:

0.370 inches

Outside Radius:

0.250 inches

First Slot/groove Width:

0.250 inches

Left-side Flange Tip Style:

Left square end

Right-side Flange Tip Style:

Right square end

Special Features:

K2 suffix material shall have a minimum bond strength of 5 pounds per 1 in. Width, z1 suffix material shall be made of chloroprene rubber and shall not contain any polymers inferior to chloroprene in ozone resistance, z2 suffix, surfaces of the material shall be free of bloom, frosting, adhesives and migrating plasticizer, z3 suffix material shall not support the growth of micro-organisms

Material:

Rubber

Material Specification:

Mil-std-417, type s, class sc, grade sc510a1b1c2e3f2k2z1z2z3 military standard single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A547c0

Mil-std (military Standard):

Mil-std-417 spec.