

View Online at <https://aerobasegroup.com/nsn/9390-00-136-9204>

**Cross Sectional Shape:**

Open channel

**Nonmetallic Hardness Rating:**

55.0 shore durometer a and 65.0 shore durometer a

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Temperature Rating:**

-40.0 degrees fahrenheit

**Overall Height:**

Between 0.386 inches and 0.426 inches

**Overall Width:**

Between 0.430 inches and 0.470 inches

**Length:**

70.600 inches

**Right Side Flange Height:**

Between 0.386 inches and 0.426 inches

**Left Side Flange Thickness:**

0.040 inches

**Right Side Flange Thickness:**

0.040 inches

**Left Side Flange Top Outer Radius:**

Between 0.141 inches and 0.171 inches

**Right Side Flange Top Outer Radius:**

Between 0.141 inches and 0.171 inches

**Environmental Protection:**

Stain and tear and low temperature and ozone resistant

**Fillet Radius Where Left Flange Joins Base Flange:**

0.020 inches

**Outer Radius Where Left Flange Joins Base Flange:**

0.090 inches

**Base Flange Thickness:**

0.060 inches

**Outer Radius Where Right Flange Joins Base Flange:**

0.090 inches

**Fillet Radius Where Right Flange Joins Base Flange:**

0.020 inches

**Left-side Flange Tip Style:**

Left offset outside radius

**Right-side Flange Tip Style:**

Right offset outside radius

**Special Features:**

Color, black

**Material:**

Rubber synthetic

**Material Specification:**

Mil-std-417, type r, class rs, grade rs615c1f1gp military standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A547c0

**Mil-std (military Standard):**

Mil-std-417 spec.