

View Online at <https://aerobasegroup.com/nsn/9390-00-248-5537>

Cross Sectional Shape:

Open channel

Nonmetallic Hardness Rating:

45.0 shore durometer a and 55.0 shore durometer a

Min. Tensile Strength (psi):

1500 pounds per square inch

Temperature Rating:

-67.0 degrees fahrenheit

Overall Height:

Between 0.500 inches and 0.620 inches

Overall Width:

Between 0.360 inches and 0.390 inches

Length:

Between 1.500 inches and 1.620 inches

Right Side Flange Height:

Between 0.387 inches and 0.483 inches

Left Side Flange Thickness:

Between 0.110 inches and 0.140 inches

Right Side Flange Thickness:

Between 0.110 inches and 0.140 inches

Left Side Flange Top Outer Radius:

0.050 inches

Left Side Flange Top Inner Radius:

0.050 inches

Right Side Flange Top Inner Radius:

0.050 inches

Right Side Flange Top Outer Radius:

0.050 inches

Environmental Protection:

Tear and low temperature and high temperature and ozone resistant and smog resistant and weather resistant

Fillet Radius Where Left Flange Joins Base Flange:

0.020 inches

Outer Radius Where Left Flange Joins Base Flange:

Between 0.105 inches and 0.135 inches

Base Flange Thickness:

Between 0.113 inches and 0.137 inches

Outer Radius Where Right Flange Joins Base Flange:

Between 0.105 inches and 0.135 inches

Fillet Radius Where Right Flange Joins Base Flange:

0.020 inches

Left-side Flange Tip Style:

Left w/inside and outside corner radii

Right-side Flange Tip Style:

Right w/inside and outside corner radii

Material:

Rubber

Material Specification:

Hms17-1527, type 3, class 50, hughes aircraft co mfr ref single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A547c0