

View Online at <https://aerobasegroup.com/nsn/9390-00-256-2819>

Cross Sectional Shape:

Open channel with round base

Nonmetallic Hardness Rating:

45.0 shore durometer a and 55.0 shore durometer a

Min. Tensile Strength (psi):

1300 pounds per square inch

Temperature Rating:

-55.0 degrees celsius and 100.0 degrees celsius

Overall Height:

0.625 inches

Overall Width:

Between 0.585 inches and 0.665 inches

Left Side Flange Thickness:

Between 0.057 inches and 0.077 inches

Right Side Flange Thickness:

Between 0.057 inches and 0.077 inches

Environmental Protection:

Craze and petroleum and low temperature and ozone resistant

First Slot/groove Depth:

Between 0.460 inches and 0.540 inches

Outside Radius:

Between 0.088 inches and 0.108 inches

First Slot/groove Width:

Between 0.002 inches and 0.102 inches

Left-side Flange Tip Style:

Left square end

Right-side Flange Tip Style:

Right square end

Special Features:

Free from cloth imprint

Material:

Rubber synthetic

Material Specification:

Mil-r-6855, class 4, type a, grade 50 military specification single material response

Specification Or Standard:

4 class and 50 grade and a type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A547c0

Mil-std (military Standard):

Mil-r-6855 spec.