

View Online at <https://aerobasegroup.com/nsn/9390-00-290-5245>

**Cross Sectional Shape:**

Semi-closed channel

**Nonmetallic Hardness Rating:**

55.0 shore durometer a and 65.0 shore durometer a

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Overall Height:**

0.187 inches

**Overall Width:**

0.625 inches

**Length:**

72.000 inches

**Right Side Flange Height:**

0.187 inches

**Left Side Flange Thickness:**

0.062 inches

**Right Side Flange Thickness:**

0.062 inches

**Left Side Top Flange Thickness:**

0.062 inches

**Right Side Top Flange Thickness:**

0.062 inches

**Left Side Top Flange Width:**

0.250 inches

**Right Side Top Flange Width:**

0.250 inches

**Outer Radius Where Left Flange Joins Top Flange:**

0.062 inches

**Outer Radius Where Right Flange Joins Top Flange:**

0.062 inches

**Environmental Protection:**

Petroleum and low temperature and ozone resistant and weather resistant

**Outer Radius Where Left Flange Joins Base Flange:**

0.062 inches

**Base Flange Thickness:**

0.062 inches

**Outer Radius Where Right Flange Joins Base Flange:**

0.062 inches

**Left-side Flange Tip Style:**

Left square end

**Right-side Flange Tip Style:**

Right square end

**Special Features:**

Free from cloth imprint

**Material:**

Rubber synthetic

**Material Specification:**

Mil-r-6855, class 2, type a, grade 60 military specification single material response

**Specification Or Standard:**

A type and 60 grade and 2 class and extruded shape form

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A547c0

**Mil-std (military Standard):**

Mil-r-6855 spec.