

View Online at <https://aerobasegroup.com/nsn/9390-00-290-5245>

Cross Sectional Shape:

Semi-closed channel

Nonmetallic Hardness Rating:

55.0 shore durometer a and 65.0 shore durometer a

Min. Tensile Strength (psi):

1500 pounds per square inch

Overall Height:

0.187 inches

Overall Width:

0.625 inches

Length:

72.000 inches

Right Side Flange Height:

0.187 inches

Left Side Flange Thickness:

0.062 inches

Right Side Flange Thickness:

0.062 inches

Left Side Top Flange Thickness:

0.062 inches

Right Side Top Flange Thickness:

0.062 inches

Left Side Top Flange Width:

0.250 inches

Right Side Top Flange Width:

0.250 inches

Outer Radius Where Left Flange Joins Top Flange:

0.062 inches

Outer Radius Where Right Flange Joins Top Flange:

0.062 inches

Environmental Protection:

Petroleum and low temperature and ozone resistant and weather resistant

Outer Radius Where Left Flange Joins Base Flange:

0.062 inches

Base Flange Thickness:

0.062 inches

Outer Radius Where Right Flange Joins Base Flange:

0.062 inches

Left-side Flange Tip Style:

Left square end

Right-side Flange Tip Style:

Right square end

Special Features:

Free from cloth imprint

Material:

Rubber synthetic

Material Specification:

Mil-r-6855, class 2, type a, grade 60 military specification single material response

Specification Or Standard:

A type and 60 grade and 2 class and extruded shape form

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A547c0

Mil-std (military Standard):

Mil-r-6855 spec.