

View Online at <https://aerobasegroup.com/nsn/9390-00-290-6770>

Cross Sectional Shape:

Open channel

Nonmetallic Hardness Rating:

55.0 shore durometer a and 65.0 shore durometer a

Min. Tensile Strength (psi):

1500 pounds per square inch

Overall Height:

0.812 inches

Overall Width:

0.437 inches

Length:

200.000 inches

Right Side Flange Height:

0.812 inches

Left Side Flange Thickness:

0.062 inches

Right Side Flange Thickness:

0.062 inches

Right Side Top Flange Thickness:

0.125 inches

Right Side Flange Top Inner Radius:

0.125 inches

Environmental Protection:

Petroleum and low temperature and ozone resistant and weather resistant

Fillet Radius Where Left Flange Joins Base Flange:

0.062 inches

Outer Radius Where Left Flange Joins Base Flange:

0.062 inches

Left Side Flange Top Radius:

0.031 inches

Base Flange Thickness:

0.062 inches

Outer Radius Where Right Flange Joins Base Flange:

0.062 inches

Fillet Radius Where Right Flange Joins Base Flange:

0.062 inches

Left-side Flange Tip Style:

Left full radius

Right-side Flange Tip Style:

Right offset/ right square w/ inside-outside radii

Special Features:

Free from cloth imprint

Material:

Rubber synthetic

Material Specification:

Mil-r-6855, class 2, type a, grade 60 military specification single material response

Specification Or Standard:

A type and 60 grade and 2 class and extruded shape form

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A547c0

Mil-std (military Standard):

Mil-r-6855 spec.