NSN 9390-00-298-6005

Nonmetallic Special Shaped Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9390-00-298-6005

Cross Sectional Shape: Hollow core, double flange Nonmetallic Hardness Rating: 45.0 shore durometer a and 55.0 shore durometer a Min. Tensile Strength (psi): 1200 pounds per square inch Overall Width: 0.562 inches Environmental Protection: Oil resistant and tear resistant and low temperature and heat dry and high temperature Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First Ytop Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material: Rubber chloroprene class cr
Nonmetallic Hardness Rating: 45.0 shore durometer a and 55.0 shore durometer a Min. Tensile Strength (psi): 1200 pounds per square inch Overall Width: 0.562 inches Environmental Protection: Oil resistant and tear resistant and low temperature and heat dry and high temperature Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
45.0 shore durometer a and 55.0 shore durometer a Min. Tensile Strength (psi): 1200 pounds per square inch Overall Width: 0.562 inches Environmental Protection: Oil resistant and tear resistant and low temperature and heat dry and high temperature Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
Min. Tensile Strength (psi): 1200 pounds per square inch Overall Width: 0.562 inches Environmental Protection: Oil resistant and tear resistant and low temperature and heat dry and high temperature Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
1200 pounds per square inch Overall Width: 0.562 inches Environmental Protection: Oil resistant and tear resistant and low temperature and heat dry and high temperature Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
Overall Width: 0.562 inches Environmental Protection: Oil resistant and tear resistant and low temperature and heat dry and high temperature Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
Environmental Protection: Oil resistant and tear resistant and low temperature and heat dry and high temperature Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
Oil resistant and tear resistant and low temperature and heat dry and high temperature Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
Inside Radius: 0.094 inches First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
First Slot/groove Depth: 0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
0.250 inches Outside Radius: 0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
0.125 inches First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
First Slot/groove Width: 0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
0.062 inches First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
First/top Flange Thickness: 0.094 inches Second Flange Thickness: 0.094 inches Material:
0.094 inches Second Flange Thickness: 0.094 inches Material:
Second Flange Thickness: 0.094 inches Material:
0.094 inches Material:
Material:
Rubber chloroprene class cr
Reference Number Differentiating Characteristics:
As differentiated by length
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A547d0