

View Online at <https://aerobasegroup.com/nsn/9390-00-454-9047>

Cross Sectional Shape:

Open channel

Nonmetallic Hardness Rating:

55.0 shore durometer a and 65.0 shore durometer a

Min. Tensile Strength (psi):

1500 pounds per square inch

Overall Height:

0.440 inches

Overall Width:

0.380 inches

Length:

100.000 inches

Right Side Flange Height:

0.440 inches

Left Side Flange Thickness:

0.062 inches

Right Side Flange Thickness:

0.062 inches

Left Side Flange Top Outer Radius:

0.015 inches

Left Side Flange Top Inner Radius:

0.015 inches

Right Side Flange Top Inner Radius:

0.015 inches

Right Side Flange Top Outer Radius:

0.015 inches

Environmental Protection:

Petroleum and low temperature and ozone resistant and weather resistant

Fillet Radius Where Left Flange Joins Base Flange:

0.022 inches

Outer Radius Where Left Flange Joins Base Flange:

0.022 inches

Base Flange Thickness:

0.062 inches

Outer Radius Where Right Flange Joins Base Flange:

0.022 inches

Fillet Radius Where Right Flange Joins Base Flange:

0.022 inches

Left-side Flange Tip Style:

Left w/inside and outside corner radii

Right-side Flange Tip Style:

Right w/inside and outside corner radii

Special Features:

Free from cloth imprint

Material:

Rubber synthetic

Material Specification:

Mil-r-6855, class 2, type a, grade 60 military specification single material response

Specification Or Standard:

2 class and extrudedshape form and 60 grade and a type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A547c0

Mil-std (military Standard):

Mil-r-6855 spec.