

View Online at <https://aerobasegroup.com/nsn/9390-00-497-3162>

**Cross Sectional Shape:**

Open channel

**Nonmetallic Hardness Rating:**

55.0 shore durometer a and 65.0 shore durometer a

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Overall Height:**

0.375 inches

**Overall Width:**

0.281 inches

**Length:**

96.000 inches

**Right Side Flange Height:**

0.375 inches

**Left Side Flange Thickness:**

0.062 inches

**Right Side Flange Thickness:**

0.062 inches

**Left Inside Angle In Deg:**

85.7

**Right Inside Angle In Deg:**

85.7

**Left Outside Angle In Deg:**

79.4

**Right Outside Angle In Deg:**

79.4

**Left Side Flange Top Outer Radius:**

0.063 inches

**Right Side Flange Top Outer Radius:**

0.063 inches

**Environmental Protection:**

Oil resistant and ozone resistant and weather resistant

**Base Flange Thickness:**

0.062 inches

**Base Flange Width:**

0.281 inches

**Left-side Flange Tip Style:**

Left w/ outside radius

**Right-side Flange Tip Style:**

Right w/ outside radius

**Special Features:**

Free from cloth imprint

**Material:**

Rubber synthetic

**Material Specification:**

Mil-r-6855, class 2, type a, grade 60 military specification single material response

**Specification Or Standard:**

A type and 60 grade and 2 class and extruded shape form

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A547c0

**Mil-std (military Standard):**

Mil-r-6855 spec.