NSN 9390-00-527-7695

Nonmetallic Special Shaped Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9390-00-527-7695

Cross Sectional Shape: Half round, hollow core Nonmetallic Hardness Rating: 55.0 shore durometer a and 65.0 shore durometer a Min. Tensile Strength (psi): 1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.312 inches Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material: Rubber chloroprene class cr
Nonmetallic Hardness Rating: 55.0 shore durometer a and 65.0 shore durometer a Min. Tensile Strength (psi): 1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.312 inches Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
55.0 shore durometer a and 65.0 shore durometer a Min. Tensile Strength (psi): 1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.312 inches Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
Min. Tensile Strength (psi): 1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.312 inches Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.312 inches Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
Overall Height: 0.375 inches Overall Width: 1.312 inches Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
O.375 inches Overall Width: 1.312 inches Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
Overall Width: 1.312 inches Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
1.312 inches Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
Environmental Protection: Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
Petroleum resistant and low temperature and ozone resistant and weather resistant Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
Inside Radius: 0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
0.205 inches Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
Base Flange Thickness: 0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
0.062 inches Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
Outside Radius: 0.250 inches First Fillet Radius: 0.125 inches Material:
0.250 inches First Fillet Radius: 0.125 inches Material:
First Fillet Radius: 0.125 inches Material:
0.125 inches Material:
Material:
Rubber chloroprene class cr
Reference Number Differentiating Characteristics:
As differentiated by length
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A547d0