NSN 9390-00-599-8509

Nonmetallic Special Shaped Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9390-00-599-8509

| Cross Sectional Shape: |
|---|
| Hollow core, double flange |
| Nonmetallic Hardness Rating: |
| 55.0 shore durometer a and 65.0 shore durometer a |
| Min. Tensile Strength (psi): |
| 1500 pounds per square inch |
| Overall Width: |
| 0.719 inches |
| Length: |
| 17.875 inches |
| Environmental Protection: |
| Oil resistant and ozone resistant and weather resistant |
| Inside Radius: |
| 0.125 inches |
| First Slot/groove Depth: |
| 0.375 inches |
| Outside Radius: |
| 0.172 inches |
| First Slot/groove Width: |
| 0.016 inches |
| First/top Flange Thickness: |
| 0.062 inches |
| Second Flange Thickness: |
| 0.062 inches |
| Material: |
| Rubber chloroprene class cr |
| Specification Or Standard: |
| A type and 60 grade and 2 class and extruded form |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A547d0 |
| Mil-std (military Standard): |
| Mil-r-6855 spec. |