NSN 9390-00-599-9521

Nonmetallic Channel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/9390-00-599-9521

Cross Sectional Shape: Open channel Nonmetallic Hardness Rating: 50.0 shore durometer a and 60.0 shore durometer a Min. Tensile Strength (psi): 1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.250 inches Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Nonmetallic Hardness Rating: 50.0 shore durometer a and 60.0 shore durometer a Min. Tensile Strength (psi): 1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.250 inches Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
50.0 shore durometer a and 60.0 shore durometer a Min. Tensile Strength (psi): 1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.250 inches Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Min. Tensile Strength (psi): 1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.250 inches Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
1500 pounds per square inch Overall Height: 0.375 inches Overall Width: 1.250 inches Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Overall Height: 0.375 inches Overall Width: 1.250 inches Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
O.375 inches Overall Width: 1.250 inches Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Overall Width: 1.250 inches Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Length: 72.000 inches Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Right Side Flange Height: 0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
0.125 inches Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Left Side Flange Thickness: 0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
0.125 inches Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Right Side Flange Thickness: 0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
0.125 inches Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Environmental Protection: Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Petroleum and low temperature and ozone resistant and weather resistant Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Base Flange Thickness: 0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
0.250 inches Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Left-side Flange Tip Style: Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Left square end Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Right-side Flange Tip Style: Right square end Special Features: Free from cloth imprint
Right square end Special Features: Free from cloth imprint
Special Features: Free from cloth imprint
Free from cloth imprint
Material:
Rubber synthetic
Material Specification:
Mil-r-6855, class 2, type a, grade 60 military specification single material response
Specification Or Standard:
2 class and extruded form and 60 grade and a type
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

A547c0

NSN 9390-00-599-9521

Nonmetallic Channel - Page 2 of 2



Mil-std (military Standard):

Mil-r-6855 spec.