

View Online at <https://aerobasegroup.com/nsn/9390-00-640-9777>

Cross Sectional Shape:

Semi-closed channel

Nonmetallic Hardness Rating:

25.0 shore durometer a and 35.0 shore durometer a

Min. Tensile Strength (psi):

1200 pounds per square inch

Overall Height:

0.218 inches

Overall Width:

1.375 inches

Right Side Flange Height:

0.218 inches

Left Side Flange Thickness:

0.093 inches

Right Side Flange Thickness:

0.093 inches

Left Side Top Flange Thickness:

0.094 inches

Right Side Top Flange Thickness:

0.094 inches

Left Side Top Flange Width:

0.343 inches

Right Side Top Flange Width:

0.343 inches

Outer Radius Where Left Flange Joins Top Flange:

0.094 inches

Outer Radius Where Right Flange Joins Top Flange:

0.094 inches

Environmental Protection:

Oil resistant and ozone resistant and weather resistant

Outer Radius Where Left Flange Joins Base Flange:

0.109 inches

Base Flange Thickness:

0.062 inches

Outer Radius Where Right Flange Joins Base Flange:

0.109 inches

Left-side Flange Tip Style:

Left square end

Right-side Flange Tip Style:

Right square end

Material:

Rubber synthetic

Material Specification:

Mil-r-6855, class 2, type a, grade 30 military specification single material response

Specification Or Standard:

A type and 30 grade and 2 class and extruded shape form

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A547c0

Mil-std (military Standard):

Mil-r-6855 spec.