

View Online at <https://aerobasegroup.com/nsn/9390-00-737-3300>

**Cross Sectional Shape:**

Open channel

**Nonmetallic Hardness Rating:**

55.0 shore durometer a and 65.0 shore durometer a

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Tempurature Rating:**

-40.0 degrees fahrenheit

**Overall Height:**

0.380 inches

**Overall Width:**

0.335 inches

**Length:**

72.000 inches

**Right Side Flange Height:**

0.380 inches

**Left Side Flange Thickness:**

0.042 inches

**Right Side Flange Thickness:**

0.042 inches

**Left Side Top Flange Thickness:**

0.100 inches

**Left Side Top Flange Width:**

0.170 inches

**Right Side Top Flange Width:**

0.170 inches

**Environmental Protection:**

Low temperature and ozone resistant

**Base Flange Thickness:**

0.060 inches

**First Slot/groove Depth:**

0.320 inches

**First Offset Height:**

0.010 inches

**Right Side Top Flange Top Thickness:**

0.100 inches

**First Offset Width:**

0.060 inches

**Left-side Flange Tip Style:**

Left offset square w/outside radius

**Right-side Flange Tip Style:**

Right offset square w/outside radius

**Special Features:**

Color, black

**Material:**

Rubber synthetic

**Material Specification:**

Mil-std-417, type r, class rs, grade rs615c1f1 military standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A547c0

**Mil-std (military Standard):**

Mil-std-417 spec.