NSN 9390-00-802-2962

Nonmetallic Special Shaped Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9390-00-802-2962

Nonn	netallic	Hardness	Ratir	ıg:
25.0	لم مسمعام			4 -

35.0 shore durometer a and 45.0 shore durometer a

Min. Tensile Strength (psi):

900 pounds per square inch

Tempurature Rating:

-40.0 degrees celsius and 100.0 degrees celsius

Overall Height:

Between 0.360 inches and 0.440 inches

Overall Width:

Between 0.222 inches and 0.320 inches

Length:

Between 120.000 inches and 144.000 inches

Right Side Flange Height:

Between 0.360 inches and 0.440 inches

Left Side Flange Thickness:

Between 0.017 inches and 0.047 inches

Right Side Flange Thickness:

Between 0.065 inches and 0.095 inches

Environmental Protection:

Corrosion and oil resistant and tear and low temperature and heat, dry and weather resistant

First Slot/groove Depth:

0.169 inches

Second Slot/groove Depth:

0.169 inches

Isthmus Width:

Between 0.047 inches and 0.077 inches

Cross Sectional Shape:

C298

Special Features:

Color, yellow, fed, std 595, 33578, matt: rubber, synthetic, chloroprene type, ams 3240

Specification Data:

81343-ams 3240 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A547d0