## NSN 9390-00-903-5577

Nonmetallic Channel - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/9390-00-903-5577                         |
|---|
| Cross Sectional Shape:  |
| Open channel  |
| Nonmetallic Hardness Rating:  |
| 55.0 shore durometer a and 65.0 shore durometer a                                     |
| Min. Tensile Strength (psi):  |
| 1500 pounds per square inch   |
| Tempurature Rating:   |
| -55.0 degrees celsius   |
| Overall Height:   |
| Between 0.187 inches and 0.196 inches   |
| Overall Width:  |
| Between 0.249 inches and 0.258 inches   |
| Right Side Flange Height:   |
| 0.156 inches  |
| Left Side Flange Thickness:   |
| Between 0.031 inches and 0.040 inches   |
| Right Side Flange Thickness:  |
| Between 0.031 inches and 0.040 inches   |
| Environmental Protection:   |
| Petroleum and low temperature and ozone resistant and weather resistant               |
| Base Flange Thickness:  |
| Between 0.031 inches and 0.040 inches   |
| Left-side Flange Tip Style:   |
| Left square end   |
| Right-side Flange Tip Style:  |
| Right square end  |
| Material:   |
| Rubber synthetic  |
| Material Specification:   |
| Mil-r-6855, class 2, type a, grade 60 military specification single material response |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A547c0  |

Mil-std (military Standard): Mil-r-6855 spec.