NSN 9390-01-072-0734

Nonmetallic Special Shaped Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9390-01-072-0734

Cross Sectional Shape: Hollow core, double flange Nonmetallic Hardness Rating: 50.0 shore durometer a and 65.0 shore durometer a Min. Tensile Strength (psi): 985 pounds per square inch Overall Width: 1.250 inches Length: Between 64.500 inches and 65.500 inches Environmental Protection:
Nonmetallic Hardness Rating: 50.0 shore durometer a and 65.0 shore durometer a Min. Tensile Strength (psi): 985 pounds per square inch Overall Width: 1.250 inches Length: Between 64.500 inches and 65.500 inches
50.0 shore durometer a and 65.0 shore durometer a Min. Tensile Strength (psi): 985 pounds per square inch Overall Width: 1.250 inches Length: Between 64.500 inches and 65.500 inches
Min. Tensile Strength (psi): 985 pounds per square inch Overall Width: 1.250 inches Length: Between 64.500 inches and 65.500 inches
985 pounds per square inch Overall Width: 1.250 inches Length: Between 64.500 inches and 65.500 inches
Overall Width: 1.250 inches Length: Between 64.500 inches and 65.500 inches
1.250 inches Length: Between 64.500 inches and 65.500 inches
Length: Between 64.500 inches and 65.500 inches
Between 64.500 inches and 65.500 inches
Environmental Protection:
Heat aging and oil resistant and ozone resistant
Inside Radius:
0.315 inches
First Slot/groove Depth:
0.500 inches
Outside Radius:
0.375 inches
First Slot/groove Width:
Between 0.219 inches and 0.229 inches
First/top Flange Thickness:
0.060 inches
Second Flange Thickness:
0.060 inches
Special Features:
Color, black
Material:
Rubber chloroprene class cr
Specification Or Standard:
Sc class and 410 grade or 415 grade or 420 grade or 510 grade or 515 grade or 520 grade and s type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A547d0
Mil-std (military Standard):
Mil-r-3065 spec.