## NSN 9515-00-516-5748

Metal Strip - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9515-00-516-5748

| Fabrication Method:   |
|---|
| Cold rolled   |
| Width:  |
| 2.500 inches  |
| Length:   |
| Between 8.000 feet and 16.000 feet                              |
| Cross-sectional Thickness:                                      |
| 0.1250 inches   |
| Cross-sectional Width:  |
| 2.500 inches  |
| Basic Shape Style:  |
| Solid   |
| Edge Type:  |
| No. 2   |
| Weight Per Unit Measure:  |
| 1.063 pounds per linear foot                                    |
| Min. Tensile Strength (psi):                                    |
| 60000 pounds per square inch                                    |
| Minimum Yield Strength:   |
| Not rated   |
| Heat Treatment:   |
| As fabricated   |
| Material:   |
| Steel, qq-s-698, comp 1015 or steel, astm a109                  |
| Material:   |
| Steel or steel, astm a109                                       |
| Material Specification:   |
| Qq-s-698, comp 1015 federal specification 1st material response |
| Surface Condition:  |
| Bright  |
| Specification Data:   |
| 81346-astm a109 professional/industrial association standard    |
| Specification Or Standard:                                      |
| 4 temper and 2 finish and 2 edge                                |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A13100  |