NSN 9535-00-269-2942

Metal Strip - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9535-00-269-2942

| га | brication Method: |
|-----|---|
| Co | ld rolled |
| Wi | dth: |
| 6.0 | 000 inches |
| Le | ngth: |
| 3.0 | 000 feet |
| Cr | oss-sectional Thickness: |
| 0.0 | 250 inches |
| Cr | oss-sectional Width: |
| 6.0 | 100 inches |
| Ba | sic Shape Style: |
| So | lid |
| Ed | де Туре: |
| Sh | eared |
| We | eight Per Unit Measure: |
| An | y acceptable |
| Mi | n. Tensile Strength (psi): |
| No | t rated |
| Mi | nimum Yield Strength: |
| No | t rated |
| He | at Treatment: |
| An | nealed |
| Ма | iterial: |
| Bra | ass, qq-b-613, alloy 260 |
| Ма | iterial: |
| Co | pper alloy 260 |
| Ма | terial Specification: |
| Qo | -b-613, alloy 260 federal specification 1st material response |
| Su | rface Condition: |
| Po | lished |
| Sp | ecification Or Standard: |
| Str | ip form and annealed temper and alloy 260 |
| Sh | elf Life: |
| N/a | a |
| Un | it Of Measure: |
| | |
| De | militarization: |
| No | |
| Fii | a. |