

View Online at <https://aerobasegroup.com/nsn/9540-00-006-8540>

**Fabrication Method:**

Extruded

**Overall Height:**

2.000 inches

**Overall Width:**

1.750 inches

**Length:**

Between 10.000 feet and 12.000 feet

**Left Side Flange Height:**

2.000 inches

**Right Side Flange Height:**

4.000 inches

**Left Side Flange Thickness:**

0.180 inches

**Right Side Flange Thickness:**

0.200 inches

**Basic Shape Style:**

H shape

**Left Side Top Flange Distance To Center Of Both Flanges:**

1.000 inches

**Left Side Bottom Flange Distance To Center Of Both Flanges:**

1.000 inches

**Right Side Top Flange Distance To Center Of Both Flanges:**

2.000 inches

**Right Side Bottom Flange Distance To Center Of Both Flanges:**

2.000 inches

**Fillet Radius Where Top Left Flange Joins Web Flange/leg:**

0.160 inches

**Fillet Radius Where Bottom Left Flange Joins Web Flange/leg:**

0.160 inches

**Fillet Radius Where Top Right Flange Joins Web Flange/leg:**

0.160 inches

**Fillet Radius Where Bottom Right Flange Joins Web Flange/leg:**

0.160 inches

**Web Flange Thickness:**

0.125 inches

**Weight Per Unit Measure:**

1.624 pounds per linear foot

**First Tip Style:**

Square end

**Second Tip Relationship To First Tip:**

Identical

**Third Tip Relationship To Preceding Tips:**

Identical w/first tip

**Fourth Tip Relationship To Preceding Tips:**

Identical w/first tip

**Right Top Inside Angle:**

90.0 degrees

**Left Top Inside Angle:**

90.0 degrees

**Left Bottom Inside Angle:**

90.0 degrees

**Right Bottom Inside Angle:**

90.0 degrees

**Heat Treatment:**

T-6 solution heat treated

**Material:**

Aluminum alloy ams-qq-a-200/11, alloy 7075

**Material:**

Aluminum alloy ams-qq-a-200/11, alloy 7075

**Specification Or Standard:**

7075 alloy and t6 temper

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A13100