NSN 9540-00-243-8926

Structural Angle - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/9540-00-243-8926

| View Online at https://aerobasegroup.com/nsn/9540-00-243-8926 |
|--|
| Fabrication Method: |
| Extruded |
| Overall Height: |
| Between 1.238 inches and 1.262 inches |
| Overall Width: |
| Between 1.238 inches and 1.262 inches |
| Length: |
| Between 10.000 feet and 12.000 feet |
| Left Side Flange Thickness: |
| Between 0.242 inches and 0.258 inches |
| Basic Shape Style: |
| Angle |
| Fillet Radius Where Left Flange Joins Base Flange: |
| Between 0.172 inches and 0.204 inches |
| Base Flange Thickness: |
| Between 0.242 inches and 0.258 inches |
| First Tip Radius: |
| Between 0.109 inches and 0.141 inches |
| Weight Per Unit Measure: |
| 0.683 pounds per linear foot |
| First Tip Style: |
| Right quarter radius |
| Second Tip Radius: |
| Between 0.109 inches and 0.141 inches |
| Second Tip Relationship To First Tip: |
| Not identical |
| Second Tip Style: |
| Upper radius |
| Left Inside Angle: |
| 90.0 degrees |
| Heat Treatment: |
| T-6511 solution heat treated and stress relieved by stretching |
| Material: |
| Aluminum alloy ams-qq-a-200/11, alloy 7075 |
| Material: |
| Aluminum alloy ams-qq-a-200/11, alloy 7075 |
| Specification Or Standard: |
| Alloy 7075, temper t6511 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 9540-00-243-8926

Structural Angle - Page 2 of 2



Demilitarization:

No

Fiig:

A13100