

View Online at <https://aerobasegroup.com/nsn/9540-00-243-9306>

**Fabrication Method:**

Extruded

**Overall Height:**

Between 2.226 inches and 2.274 inches

**Length:**

Between 10.000 feet and 12.000 feet

**Left Side Top Flange Thickness:**

Between 0.149 inches and 0.163 inches

**Right Side Top Flange Thickness:**

Between 0.149 inches and 0.163 inches

**Basic Shape Style:**

T shape

**Leg Thickness:**

Between 0.149 inches and 0.163 inches

**Left Side Top Flange Distance To Center Of Both Flanges:**

Between 1.106 inches and 1.138 inches

**Right Side Top Flange Distance To Center Of Both Flanges:**

Between 1.772 inches and 1.804 inches

**Fillet Radius Where Top Left Flange Joins Web Flange/leg:**

Between 0.109 inches and 0.141 inches

**Fillet Radius Where Top Right Flange Joins Web Flange/leg:**

Between 0.109 inches and 0.141 inches

**Top Flange Width:**

Between 2.886 inches and 2.934 inches

**Weight Per Unit Measure:**

0.956 pounds per linear foot

**First Tip Style:**

Square w/ inner and outer corner radii

**First Tip Inner Radius:**

Between 0.016 inches and 0.048 inches

**First Tip Outer Radius:**

Between 0.016 inches and 0.048 inches

**Second Tip Relationship To First Tip:**

Identical

**Third Tip Relationship To Preceding Tips:**

Identical w/first tip

**Right Top Inside Angle:**

82.0 degrees

**Left Top Inside Angle:**

98.0 degrees

**Heat Treatment:**

T-6511 solution heat treated and stress relieved by stretching

**Material:**

Aluminum alloy ams-qq-a-200/11, alloy 7075

**Material:**

Aluminum alloy ams-qq-a-200/11, alloy 7075

**Specification Or Standard:**

7075 composition and t6511 temper

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A13100