

View Online at <https://aerobasegroup.com/nsn/9540-00-288-0525>

Fabrication Method:

Extruded

Overall Width:

2.000 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Flange Height:

0.938 inches

Right Side Flange Height:

0.938 inches

Left Side Flange Thickness:

0.125 inches

Right Side Flange Thickness:

0.125 inches

Distance Between Flanges:

0.190 inches

Basic Shape Style:

Channel

Fillet Radius Where Left Flange Joins Base Flange:

0.094 inches

Outer Radius Where Left Flange Joins Base Flange:

0.094 inches

Base Flange Thickness:

0.125 inches

Outer Radius Where Right Flange Joins Base Flange:

0.094 inches

Fillet Radius Where Right Flange Joins Base Flange:

0.094 inches

Right Side Bottom Flange Thickness:

0.125 inches

Left Side Bottom Flange Thickness:

0.125 inches

Right Side Distance To Center Of Both Flanges:

1.000 inches

Left Side Distance To Center Of Both Flanges:

1.000 inches

Weight Per Unit Measure:

0.600 pounds per linear foot

First Tip Style:

Square w/ inner and outer corner radii

First Tip Inner Radius:

0.031 inches

First Tip Outer Radius:

0.031 inches

Second Tip Relationship To First Tip:

Identical

Third Tip Relationship To Preceding Tips:

Identical w/first tip

Fourth Tip Relationship To Preceding Tips:

Identical w/first tip

Left Inside Angle:

90.0 degrees

Right Inside Angle:

90.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy, qq-a-200/11

Material:

Aluminum alloy 7075

Specification Or Standard:

T6 temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A13100