

View Online at <https://aerobasegroup.com/nsn/9540-00-414-3793>

Fabrication Method:

Extruded

Overall Width:

4.320 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Flange Height:

1.354 inches

Right Side Flange Height:

1.354 inches

Left Side Flange Thickness:

0.094 inches

Right Side Flange Thickness:

0.094 inches

Left Side Top Flange Thickness:

0.094 inches

Right Side Top Flange Thickness:

0.094 inches

Left Side Top Flange Width:

1.600 inches

Right Side Top Flange Width:

1.600 inches

Outer Radius Where Left Flange Joins Top Flange:

0.031 inches

Fillet Radius Where Left Flange Joins Top Flange:

0.100 inches

Outer Radius Where Right Flange Joins Top Flange:

0.031 inches

Fillet Radius Where Right Flange Joins Top Flange:

0.100 inches

Basic Shape Style:

Channel

Fillet Radius Where Left Flange Joins Base Flange:

0.100 inches

Outer Radius Where Left Flange Joins Base Flange:

0.031 inches

Base Flange Thickness:

0.094 inches

Base Flange Width:

1.120 inches

Outer Radius Where Right Flange Joins Base Flange:

0.031 inches

Fillet Radius Where Right Flange Joins Base Flange:

0.100 inches

Weight Per Unit Measure:

0.780 pounds per linear foot

First Tip Style:

Square w/ inner and outer corner radii

First Tip Inner Radius:

0.031 inches

First Tip Outer Radius:

0.031 inches

Second Tip Relationship To First Tip:

Identical

Left Inside Angle:

90.0 degrees

Right Inside Angle:

90.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy ams-qq-a-200/11, alloy 7075

Material:

Aluminum alloy ams-qq-a-200/11, alloy 7075

Specification Or Standard:

T6 temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A13100