

View Online at <https://aerobasegroup.com/nsn/9540-00-450-5851>

Fabrication Method:

Extruded

Overall Width:

2.400 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Flange Height:

1.550 inches

Right Side Flange Height:

1.550 inches

Left Side Flange Thickness:

0.120 inches

Right Side Flange Thickness:

0.120 inches

Distance Between Flanges:

0.500 inches

Basic Shape Style:

Channel

Fillet Radius Where Left Flange Joins Base Flange:

0.250 inches

Outer Radius Where Left Flange Joins Base Flange:

0.150 inches

Base Flange Thickness:

0.120 inches

Outer Radius Where Right Flange Joins Base Flange:

0.150 inches

Fillet Radius Where Right Flange Joins Base Flange:

0.250 inches

Right Side Bottom Flange Thickness:

0.120 inches

Left Side Bottom Flange Thickness:

0.120 inches

Right Side Distance To Center Of Both Flanges:

1.200 inches

Left Side Distance To Center Of Both Flanges:

1.200 inches

Weight Per Unit Measure:

0.802 pounds per linear foot

First Tip Style:

Square end

Second Tip Relationship To First Tip:

Identical

Third Tip Relationship To Preceding Tips:

Identical w/first tip

Fourth Tip Relationship To Preceding Tips:

Identical w/first tip

Left Inside Angle:

90.0 degrees

Right Inside Angle:

90.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy ams-qq-a-200/11, alloy 7075

Material:

Aluminum alloy ams-qq-a-200/11, alloy 7075

Specification Or Standard:

T6 temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A13100