

View Online at <https://aerobasegroup.com/nsn/9540-00-595-7553>

**Fabrication Method:**

Extruded

**Overall Width:**

1.750 inches

**Length:**

Between 10.000 feet and 132.000 feet

**Left Side Flange Height:**

1.000 inches

**Right Side Flange Height:**

1.000 inches

**Left Side Flange Thickness:**

0.125 inches

**Right Side Flange Thickness:**

0.125 inches

**Left Side Top Flange Thickness:**

0.122 inches

**Right Side Top Flange Thickness:**

0.122 inches

**Left Side Top Flange Width:**

0.562 inches

**Right Side Top Flange Width:**

0.562 inches

**Outer Radius Where Left Flange Joins Top Flange:**

0.125 inches

**Fillet Radius Where Left Flange Joins Top Flange:**

0.062 inches

**Outer Radius Where Right Flange Joins Top Flange:**

0.125 inches

**Fillet Radius Where Right Flange Joins Top Flange:**

0.062 inches

**Basic Shape Style:**

Channel

**Fillet Radius Where Left Flange Joins Base Flange:**

0.062 inches

**Outer Radius Where Left Flange Joins Base Flange:**

0.125 inches

**Base Flange Thickness:**

0.123 inches

**Outer Radius Where Right Flange Joins Base Flange:**

0.125 inches

**Fillet Radius Where Right Flange Joins Base Flange:**

0.062 inches

**Weight Per Unit Measure:**

0.640 pounds per linear foot

**First Tip Style:**

Square end

**Second Tip Relationship To First Tip:**

Identical

**Left Inside Angle:**

90.0 degrees

**Right Inside Angle:**

90.0 degrees

**Heat Treatment:**

T-4 solution heat treated

**Material:**

Aluminum alloy ams-qq-a-200/3, alloy 2024

**Material:**

Aluminum alloy ams-qq-a-200/3, alloy 2024

**Specification Or Standard:**

T4 temper

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A13100