

View Online at <https://aerobasegroup.com/nsn/9540-00-595-8597>

Fabrication Method:

Extruded

Overall Height:

1.875 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Top Flange Thickness:

0.064 inches

Basic Shape Style:

Z shape

Right Side Bottom Flange Thickness:

0.064 inches

Fillet Radius Where Top Left Flange Joins Web Flange/leg:

0.125 inches

Fillet Radius Where Bottom Right Flange Joins Web Flange/leg:

0.125 inches

Web Flange Thickness:

0.064 inches

Top Flange Width:

0.750 inches

Bottom Flange Width:

0.938 inches

Outer Radius Where Top Left Flange Joins Web Flange:

0.125 inches

Weight Per Unit Measure:

0.310 pounds per linear foot

First Tip Style:

Flange left downward w/ square end and inner and outer corner radii

First Tip Inner Corner Radius:

0.125 inches

Second Tip Inner Corner Radius:

0.125 inches

First Tip Outer Corner Radius:

0.125 inches

First Tip Thickness:

0.064 inches

Second Tip Thickness:

0.064 inches

First Tip Flange Height:

0.250 inches

Second Tip Flange Height:

0.189 inches

Second Tip Relationship To First Tip:

Not identical

Second Tip Style:

Flange right upward with square end, inner corner radius, and square outer corner

Left Top Inside Angle:

90.0 degrees

Right Bottom Inside Angle:

90.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy, qq-a-200/11

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-200/11 federal specification 1st material response

Specification Or Standard:

T6 temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A13100