

View Online at <https://aerobasegroup.com/nsn/9540-00-805-0465>

**Fabrication Method:**

Extruded

**Overall Height:**

1.250 inches

**Length:**

Between 10.000 feet and 12.000 feet

**Left Side Top Flange Thickness:**

0.150 inches

**Right Side Top Flange Thickness:**

0.150 inches

**Basic Shape Style:**

T shape

**Leg Thickness:**

0.125 inches

**Left Side Top Flange Distance To Center Of Both Flanges:**

0.930 inches

**Right Side Top Flange Distance To Center Of Both Flanges:**

0.930 inches

**Fillet Radius Where Top Left Flange Joins Web Flange/leg:**

0.125 inches

**Fillet Radius Where Top Right Flange Joins Web Flange/leg:**

0.125 inches

**Top Flange Width:**

1.860 inches

**Weight Per Unit Measure:**

0.710 pounds per linear foot

**First Tip Style:**

Square end

**Third Tip Inner Radius:**

0.125 inches

**Third Tip Outer Radius:**

0.125 inches

**Third Tip Diameter:**

0.600 inches

**Second Tip Relationship To First Tip:**

Identical

**Third Tip Relationship To Preceding Tips:**

Not identical

**Third Tip Style:**

Full diameter

**Right Top Inside Angle:**

90.0 degrees

**Left Top Inside Angle:**

90.0 degrees

**Heat Treatment:**

T-6 solution heat treated

**Material:**

Aluminum alloy, qq-a-200/11

**Material:**

Aluminum alloy 7075

**Material Specification:**

Qq-a-200/11 federal specification 1st material response

**Specification Or Standard:**

T6 temper

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A13100