

View Online at <https://aerobasegroup.com/nsn/9540-00-982-2589>

Fabrication Method:

Extruded

Overall Height:

3.000 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Top Flange Thickness:

0.270 inches

Right Side Top Flange Thickness:

0.270 inches

Basic Shape Style:

I shape

First Tip Radius:

0.100 inches

Right Side Bottom Flange Thickness:

0.270 inches

Left Side Bottom Flange Thickness:

0.270 inches

Left Side Top Flange Distance To Center Of Both Flanges:

1.254 inches

Left Side Bottom Flange Distance To Center Of Both Flanges:

1.254 inches

Right Side Top Flange Distance To Center Of Both Flanges:

1.254 inches

Right Side Bottom Flange Distance To Center Of Both Flanges:

1.254 inches

Web Flange Thickness:

0.349 inches

Top Flange Width:

2.509 inches

Bottom Flange Width:

2.509 inches

Left Side Top Flange Tip Thickness:

0.170 inches

Left Side Bottom Flange Tip Thickness:

0.170 inches

Right Side Top Flange Tip Thickness:

0.170 inches

Right Side Bottom Flange Tip Thickness:

0.170 inches

Weight Per Unit Measure:

2.670 pounds per linear foot

First Tip Style:

Lower radius

Second Tip Radius:

0.100 inches

Third Tip Radius:

0.100 inches

Fourth Tip Radius:

0.100 inches

Second Tip Relationship To First Tip:

Identical

Third Tip Relationship To Preceding Tips:

Not identical

Third Tip Style:

Upper radius

Fourth Tip Relationship To Preceding Tips:

Identical w/third tip

Left Top Inner Face To Outer Face Angle:

90.0 degrees

Right Top Inner Face To Outer Face Angle:

90.0 degrees

Right Bottom Inner Face To Outer Face Angle:

90.0 degrees

Left Bottom Inner Face To Outer Face Angle:

90.0 degrees

Heat Treatment:

T-6 solution heat treated or artificially aged

Material:

Aluminum alloy 6061 or aluminum alloy 6062

Material Specification:

Qq-a-200/8 federal specification 1st material response

Specification Or Standard:

T6 temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A13100