

View Online at <https://aerobasegroup.com/nsn/9540-00-984-7307>

Fabrication Method:

Extruded

Overall Width:

2.125 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Flange Height:

0.750 inches

Right Side Flange Height:

0.750 inches

Left Side Flange Thickness:

0.050 inches

Right Side Flange Thickness:

0.050 inches

Left Side Top Flange Thickness:

0.050 inches

Right Side Top Flange Thickness:

0.050 inches

Left Side Top Flange Width:

0.675 inches

Right Side Top Flange Width:

0.675 inches

Outer Radius Where Left Flange Joins Top Flange:

0.031 inches

Fillet Radius Where Left Flange Joins Top Flange:

0.094 inches

Outer Radius Where Right Flange Joins Top Flange:

0.031 inches

Fillet Radius Where Right Flange Joins Top Flange:

0.094 inches

Basic Shape Style:

Channel

Fillet Radius Where Left Flange Joins Base Flange:

0.094 inches

Outer Radius Where Left Flange Joins Base Flange:

0.031 inches

Base Flange Thickness:

0.050 inches

Base Flange Width:

0.875 inches

Outer Radius Where Right Flange Joins Base Flange:

0.031 inches

Fillet Radius Where Right Flange Joins Base Flange:

0.094 inches

Weight Per Unit Measure:

0.220 pounds per linear foot

First Tip Style:

Square end

Second Tip Relationship To First Tip:

Identical

Left Inside Angle:

90.0 degrees

Right Inside Angle:

90.0 degrees

Heat Treatment:

O-annealed

Material:

Aluminum alloy ams-qq-a-200/3, alloy 2024

Material:

Aluminum alloy ams-qq-a-200/3, alloy 2024

Specification Or Standard:

0 temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A13100