

View Online at <https://aerobasegroup.com/nsn/9540-01-072-0174>

Fabrication Method:

Extruded

Overall Height:

2.120 inches

Length:

Between 10.000 feet and 12.000 feet

Left Side Top Flange Thickness:

0.100 inches

Right Side Top Flange Thickness:

0.100 inches

Basic Shape Style:

T shape

Leg Thickness:

0.100 inches

Left Side Top Flange Distance To Center Of Both Flanges:

1.750 inches

Right Side Top Flange Distance To Center Of Both Flanges:

1.750 inches

Fillet Radius Where Top Left Flange Joins Web Flange/leg:

0.125 inches

Fillet Radius Where Top Right Flange Joins Web Flange/leg:

0.125 inches

Top Flange Width:

3.500 inches

Weight Per Unit Measure:

0.670 pounds per linear foot

First Tip Style:

Square end

Second Tip Relationship To First Tip:

Identical

Third Tip Relationship To Preceding Tips:

Identical w/first tip

Right Top Inside Angle:

90.0 degrees

Left Top Inside Angle:

90.0 degrees

Heat Treatment:

O-annealed

Material:

Aluminum alloy ams-qq-a-200/3, alloy 2024

Material:

Aluminum alloy ams-qq-a-200/3, alloy 2024

Specification Data:

81755-k40 manufacturers standard

Specification Or Standard:

O temper

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A13100