

View Online at <https://aerobasegroup.com/nsn/9540-01-110-4784>

**Fabrication Method:**

Extruded

**Overall Height:**

Between 5.016 inches and 5.084 inches

**Length:**

Between 10.000 feet and 12.000 feet

**Left Side Top Flange Thickness:**

Between 0.621 inches and 0.639 inches

**Right Side Top Flange Thickness:**

Between 0.591 inches and 0.609 inches

**Basic Shape Style:**

T shape

**Leg Thickness:**

Between 0.571 inches and 0.589 inches

**Left Side Top Flange Distance To Center Of Both Flanges:**

Between 2.216 inches and 2.264 inches

**Right Side Top Flange Distance To Center Of Both Flanges:**

Between 2.816 inches and 2.864 inches

**Fillet Radius Where Top Left Flange Joins Web Flange/leg:**

Between 0.225 inches and 0.275 inches

**Fillet Radius Where Top Right Flange Joins Web Flange/leg:**

Between 0.225 inches and 0.275 inches

**Top Flange Width:**

Between 5.046 inches and 5.114 inches

**Weight Per Unit Measure:**

6.908 pounds per linear foot

**First Tip Style:**

Square w/ inner and outer corner radii

**First Tip Inner Radius:**

Between 0.015 inches and 0.047 inches

**First Tip Outer Radius:**

Between 0.015 inches and 0.047 inches

**Second Tip Relationship To First Tip:**

Identical

**Third Tip Relationship To Preceding Tips:**

Identical w/first tip

**Right Top Inside Angle:**

Between 89.7 degrees and 92.3 degrees

**Left Top Inside Angle:**

89.0 degrees

**Heat Treatment:**

T-6511 solution heat treated

**Material:**

Aluminum alloy ams-qq-a-200/11, alloy 7075

**Material:**

Aluminum alloy ams-qq-a-200/11, alloy 7075

**Specification Or Standard:**

7075 alloy and t6511 temper

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A13100